

[Belinea 10 15 51]


Convincing performance, superior design,
surprising price

With the Belinea 10 15 51 MAXDATA launches a 15-inch entry display in elegant SilverBlackStyle.

Not only the pleasing appearance of the housing but also the technical design of the TFT monitor prove Belinea's usually high performance. Excellent contrast and brightness values result in a very good picture performance, and due to the integrated power supply and the built-in-speakers you have more room on your desk top. Prepared for wall mountings according to the VESA standard and certified according to TÜV Ergo this TFT fulfils all requirements for a pleasant working environment. Furthermore the Belinea 10 15 51 is certified according to the latest and strictest TCO03 standard, hence it's one of the first 15-inch TFTs worldwide which are distinguished by this certification. Considering this convincing performance, the price will surprise you.



SilverBlackStyle



Integrated speaker
for multimedia
applications



D-Sub connection
for analogue
graphic cards



Belinea 10 15 51 – The office standard in SilverBlackStyle

- 15 inch (38.1 cm)
- analogue
- Sound, TN-Panel
- Viewing angle: 130° / 110°
- Response time rise / fall: 9 / 16 ms

Target Groups

- Small and Medium Business
- Price sensitive users
- Representative Workstations

Belinea 10 15 51 – Technical Data

Panel characteristics

Image size	15"
Viewable image size in inch / cm	15" / 38.1
Max. picture size (w x h) in mm	304.1 x 228.1
Physical resolution	1024 x 768
Pixel pitch in mm	0.297 x 0.297
Active Matrix TFT	•
Displayable colours (max.)	TN / CPT
Brightness in cd / qm	16 Mio (Dither)
Contrast ratio	250
Viewing angle horizontal	400:1
Viewing angle vertical	130°
Response time: rise / fall in ms	110°
Coating	9 / 16
Panel technology / manufacturer	Anti Glare
Backlight	2 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 61
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	80
Input voltage 110-230V, 50-60Hz	•
Power consumption in Watt (On / Sleep)	40 / 1
Input signal (VGA-card) analog / digital	• / -
Output audio amplifier	2 x 1 Watt

Features

Factory / user defined modes	12 / 9
OSD	•
Integrated speaker	•
Power supply in the panel/in the stand / external	• / - / -
Tilt back / forth	20° / 5°

Controls

brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	external / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	- / •
Zoom / frequency	- / •
Recall / video signal selection	• / -
OSD position / OSD language(s)	• / 5
Mute	external
Volume	external

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	-
1280 x 1024	-

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / •
TCO03	•
TÜV GS / TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc.to VESA standard	•
MAC compliant	•

Connections

15 pin. Mini-D-Sub	•
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect. 15 pin. Mini-D-Sub	• (non detachable)
Audio cable	•
Wall mounting (option)	on demand

Physical specification

Size (w x h x d) in mm	340 x 352 x 182
Net / gross weight in kg	2,8 / 4,7

Austria

MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux

MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal

MAXDATA Iberia
c/ Collado mediano, s/n • Edificio Prisma
Portal 1-Pta. 1ª B • E-28230-Las ROZAS, Madrid

France

MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY Cedex

Germany

MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45768 Marl

Italy

MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland

MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Pulawska 303
02-785 Warszawa

Switzerland

MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom

MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: